SPARTAN®

Everyday solution for short or medium term well suspension

The SPARTAN® is designed for well suspension periods of days to months, ensuring easy deployment, a secure seal and safe removal on task completion.



Benefits

- Absolute protection
- Confidence in retrieval
- Easy and rapid deployment
- Reduces operational time
- Safer and lower cost operations
- Flexible set depths and angles

Specifications

Sizes, inches	9 5/8" — 14"
Pressure rating, psi [bar]	3,000 — 12,500 [207 — 862]
Temperature rating, °F [°C]	35 – 203 [2 – 95]
ISO 14310 qualified	Yes
Max hang-off weight, klbs [tons]	250 [113]
Through-bore diameter, inches	1.96 – 3
Typical suspension period	Days to Months
Drillpipe Connections	NC50 — 6 f/8 FH
Elastomer	HNBR — FKM
Ball valve ISO 28781 qualified	Yes

Specifications may be subject to change.

Features - ISO 14310 V3 to V6 certified seal - 100% retrieval record; millable - No set weight needed below - High differential pressure elements up to 12,500 psi and 95°C - Seal testable from above and below - Sizes 9 5/8" - 14" clients. We are Archer.

Archer is a global oil services company with a heritage that stretches back over 40 years. With a strong focus on safety and delivering the highest quality products and services, Archer operates in 40 locations over 19 countries providing drilling services, well integrity & intervention, plug & abandonment and decommissioning to its upstream oil and gas

