

## 3,5" Releasable Overshot

### Description

This overshot is designed to withstand jarring forces experienced during fishing operations.

To release from the fish, jar down and shear pins inserted to match the down forces. The shear-pin on this overshot is located in the top-sub. This requires no contact with the inner core to be able to release, and you will be able to release and retrieve the tool in most situations.

All components has been exposed to comprehensive testing to provide a safe controlled release of down hole equipment.

The overshot can be supplied with different grapples making it possible to engage fishes from 1,375" to 2,5"

### Specifications

Tool OD	<b>3,5 in / 88,9 mm</b>
Tool length	<b>34,78 in / 883,4 mm</b>
Tool Weight	<b>48,4 lbs / 22 kg</b>
Fishing neck	<b>2,31 in / 58,67 mm</b>
Top connection	<b>2-1/2" and 1-7/8" QLS 1-9/16" SR</b>
Metal quality	<b>Standard Service</b>
Minimum tensile rating	<b>89 Klbs / 40454 kg</b>
Reach	<b>30 mm – 165 mm (Custom- max reach: 225mm)</b>
Grapple range	<b>1,375" – 2,5"</b>
Bell Guides	<b>Available upon request</b>
IFS Part Nr	<b>1306600</b>

# Archer

#### Archer

Finnestadveien 24  
P.O. Box 338  
N-4002 Stavanger  
Norway  
Tel: +4751308000  
[archerwell.com](http://archerwell.com)