

# 4,25" OD HD Slick Catch Overshot

## Description

The HD Slick-Catch Overshot engages the fish with a 360 degree collet/grapple. The grapple has special treated grip area to withstand heavy jarring.

To release from the fish, jar down and shear pins inserted to match the down forces.

The overshot has been designed to withstand heavy duty jarring/impact force, and all components has been exposed to comprehensive testing to provide a safe controlled release of down hole equipment.

The overshot can be supplied with different grapples making it possible to engage fishes from 2,5" to 3,25"

**\*With use off 3,56-3,69" grapple, 4,45" OD housing is needed**

The overshot will preferably be run with a Bell Guide to help guide the fish into the overshot. This will give the tool a bigger OD depending on

## Specifications

Tool OD	4,25 in / 108 mm
Tool length	46,1 in / 1172 mm
Tool Weight	121 lbs / 55 kg
Fishing neck	2,312 in / 58,74 mm
Top connection	2-7/8" HD EasyConnect
Metal quality	Standard Service
Yield	200 Klbs / 90680 kg
Ultimate Tensile strength	230 Klbs / 104325 kg
Grapple reach	2,5" – 3,69"*
Reach	138 mm – 258 mm
Available Bell Guides	4,75"/ 4,88"/ 5,5"
IFS Part Nr	1306598

# Archer

## Archer

Finnestadveien 24  
P.O. Box 338  
N-4002 Stavanger  
Norway  
Tel: +4751308000  
archerwell.com