Production logging tools High resolution measurements



Production logging tools provide high resolution measurements of the fluid compositions and flow rates in the downhole environment that are used to evaluate well performance. A typical production logging toolstring is comprised of multiple sensors covering a range of physical measurements in order to identify fluid types, volumes and rates of their production or injection. Each of these measurements is digitised and recorded in order to create a comprehensive profile of the wellbore environment.

The combination of sensors and their configuration may be tailored to suit producing or injecting wells and to resolve single-phase, two-phase or three-phase flow regimes. Tools come in a range of sizes to provide optimal coverage and resolution across a range of tubular diameters. Production logging tools can be deployed in surface read out or memory configurations and can be combined with integrity or other diagnostic services to meet customer specific requirements.

Features

- High resolution measurements
- Fast response and low threshold sensors
- Combination with other tools/services
- Memory or surface read-out configurations
- Corrosion resistant materials

Key benefits

- Single-phase, two-phase and three-phase fluid quantification
- Coverage of several pipe sizes
- Easy to operate and use
- Operates in wide range of well conditions

Typical applications

- Production/injection profiling
- Zonal contribution evaluation
- Stimulation performance evaluation
- Water break-through identification





Toolstring composition

Measurement	Sensor technology	Resolution
Temperature	Platinum resistance	0.003 °C
Pressure	Quartzdyne pressure gauge	0.008 psi
Correlation	Gamma ray Collar locator	3.0 Counts/API NA
Water hold-up	Capacitance	O.1%
Fluid density	Radioactive absorption Inertial response	0.01 g/cc 0.01 g/cc
Flow meter	Full bore & Inline spinner	10 pulses/revolution

Photos courtesy of GE Oil & Gas

Toolstring specification

Temperature Rating, degF [degC]	350 [177°C]
Pressure Rating, psi [MPa]	15,000 [103.4]
Toolstring Diameter (Max), in [mm]	2 1/8 [54]
Toolstring Length, in [m]	336.8 [8.55]
Toolstring Weight, lb [kg]	140.2 [63.6]
Toolbus	Ultrawire
Maximum opening	Up to 7 in casing
Materials	Corrosion resistant throughout

Archer

Pavilion 5, Howe Moss Drive Kirkhill Business Park Aberdeen, AB21 OGL United Kingdom T + 44 1224 767524

We are a global oilfield service company that specialises in drilling services and well services because we believe that specialists do the job best. Our experience drives our difference in our constant search for new ways to deliver better wells. We listen to our customers to provide straightforward solutions to help them produce more oil and gas. We are craftsmen, who take pride in our work and do what we promise. **We are Archer, the well company.**

